










Vaddio™ EZCamera™ Cabling Products

EZCamera System Cabling Distances

Vaddio Camera System	System Image	Stock PowerRite™ Power Supply	Max. Power,/Video, Cat. 5 Cable Length	Optional Power Supply Cable Distances
WallVIEW 100 PTZ 999-2204-000 (NTSC) 999-2204-001 (PAL)		18VDC	115' (35.1m)	*Optional 24 VDC 115' to 250' (35.1m to 76.2m) Not for use below 115'
WallVIEW 70 PTZ 999-2704-000 (NTSC) 999-2704-001 (PAL)		18VDC	200' (61m)	*Optional 24 VDC 200' to 300' (61m to 91.4m) Not for use below 200'
WallVIEW 50i PTZ 999-4204-000 (NTSC) 999-4204-001 (PAL)		18VDC	185' / 56.4m	*Optional 24 VDC 185' to 275' (56.4m to 83.8m) Not for use below 185'
CeilingVIEW™ 70 PTZ HideAway 999-2404-000 (NTSC) 999-2404-001 (PAL)		18VDC	157' / 47.8m	NA
CeilingVIEW 70 PTZ 999-2304-000 (NTSC) 999-2304-001 (PAL)				
WallVIEW 50i PTZ HideAway 999-4404-000 (NTSC) 999-4404-001 (PAL)		18VDC	150' / (45.7m)	NA

Vaddio Camera System	System Image	Optional Power Supplies	Max. Power,/Video, Cat. 5 Cable Length	Optional Power Supply Cable Distances
Model 100 PTZ 999-2001-100 (NTSC) 999-2001-101 (PAL)		Optional 18 VDC PowerRite or Quick-Connect 4 (18VDC x 4)	115' (35.1m)	*Optional 24 VDC 115' to 250' (35.1m to 76.2m) Not for use below 115'
Model 70 PTZ 999-2001-070 (NTSC) 999-2001-071 (PAL)		Optional 18 VDC PowerRite or Quick-Connect 4 (18VDC x 4)	200' (60.1m)	*Optional 24 VDC 200' to 300' (61m to 91.4m) Not for use below 200'
Model 50i PTZ 999-2001-050 (NTSC) 999-2001-051 (PAL)		Optional 18 VDC PowerRite or Quick-Connect 4 (18VDC x 4)	185' (56.4m)	*Optional 24 VDC 185' to 275' (56.4m to 83.8m) Not for use below 185'
Model 50iR PTZ 999-2001-060 (NTSC) 999-2001-061 (PAL)				

*For WallVIEW or Model PTZ Systems with EZCamera Cable Shoes shipped after Jan. 1st, 2007 only.

Vaddio™ PRO, CCU and CeilingVIEW Series Cabling Products
HSDS™ System Cabling Distances

Vaddio Camera System	System Image	PowerRite™ Power Supply	Max. Power,/Video, Cat. 5 Cable Length
WallVIEW™ PRO & CCU 300 999-6205-000 (NTSC) 999-6205-001 (PAL) 999-6207-000 (NTSC) 999-6207-001 (PAL)		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
WallVIEW™ PRO & CCU HD1 999-6305-000 (NTSC) 999-6305-001 (PAL) 999-6307-000 (NTSC) 999-6307-001 (PAL)		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
WallVIEW™ PRO EagleEye® 999-9500-000 (NTSC) 999-9500-001 (PAL)		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
WallVIEW™ PRO & CCU Z700 999-6805-000 (NTSC) 999-6805-001 (PAL) 999-6807-000 (NTSC) 999-6807-001 (PAL)		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
WallVIEW™ PRO & CCU H700 999-6704-000 (NTSC) 999-6704-001 (PAL) 999-6707-000 (NTSC) 999-6707-001 (PAL)		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
WallVIEW™ PRO & CCU HE100 999-6105-000 (NTSC) 999-6105-001 (PAL) 999-6107-000 (NTSC) 999-6107-001 (PAL)		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
Add-A-Cam PRO For Canon® and Sony® Camcorders 999-6500-000 (North America) 999-6500-001 (International) Shown with optional Canon XH-A1 Camcorder		36 VDC	500' (152.4 m) Using High Speed Differential Signaling
CeilingVIEW SD & CCU Document Camera 999-2008-000 (NTSC) 999-2008-001 (PAL) 999-2009-000 (NTSC) 999-2009-001 (PAL)		24 VDC	500' (152.4 m) Using High Speed Differential Signaling
CeilingVIEW HD & CCU Document Camera 999-3008-000 (NTSC) 999-3008-001 (PAL) 999-3009-000 (NTSC) 999-3009-001 (PAL)		24 VDC	500' (152.4 m) Using High Speed Differential Signaling